

## LED PAR30 Lamp/ Long Neck



SATCO High Performance LED PAR30 lamps, feature a "High Power Chip" configuration specifically designed to illuminate objects, displays, showcases, etc. Delivering comparable light output to halogen "PAR30" lamps. The LED PAR30 design directly replaces existing halogen lamps and maintains the lamps proportions in the luminaire while optimizing performance.

### Applications

- Display & showcase lighting
- Recessed & track lighting
- Retail merchandising



# LED PAR30 Lamp

## Long neck

### Features and Benefits

- Long life – 50,000 hours
- High efficiency – only 13 watts
- Offered in 3200K & 6500K
- Attractive design – seamless integration
- No IR or UV – protects valuable objects
- Instant on at full brightness
- Mercury free – environmentally positive
- Very low maintenance costs
- Reduces cooling costs – generates very little heat
- 3 year warranty
- C.U.L. listed



### LED PAR30/ Long Neck – E26 Base

#### Specifications

Parameter	Unit	Specification			
Color Temperature	K	3200K		6500K	
Beam Angle	deg.	25°	40°	25°	40°
Power Consumption	W	13			
Operating Voltage	V	120			
Luminous Flux	lm	555	555	640	640
Life Time	Hrs.	50000			
Dimensions	inch	Ø3.70" W x 4.50" H			
Base		E26			
Color Rendering Index	Ra	83		76	
Item No.		<b>S8771</b>	<b>S8773</b>	<b>S8772</b>	<b>S8774</b>

#### Illumination

Throw Distance	6500K – 25°		3200K – 25°		6500K – 40°		3200K – 40°	
	Beam width	Luminance (lux)	Beam width	Luminance (lux)	Beam width	Luminance (lux)	Beam width	Luminance (lux)
3.5 Ft.	1.57 Ft.	8237	1.57 Ft.	6739	2.40 Ft.	1050	2.40 Ft.	960
6.5 Ft.	2.46 Ft.	2982	2.46 Ft.	1689	3.50 Ft.	263	3.50 Ft.	250
9.8 Ft.	2.95 Ft.	923	2.95 Ft.	749	4.26 Ft.	118	4.26 Ft.	107

Item No.	Watt	Lumens	CCT	Beam	Volt	Life/ Hrs.	M.O.D.(Inches)	M.O.L.(Inches)	ES	CUFT.	Unit UPC	Case UPC
<b>S8771</b>	13	555	3200K	25°	120	50000	3.70	4.50	N	1.44	045923087714	10045923087711
<b>S8772</b>	13	640	6500K	25°	120	50000	3.70	4.50	N	1.44	045923087721	10045923087728
<b>S8773</b>	13	555	3200K	40°	120	50000	3.70	4.50	N	1.44	045923087738	10045923087735
<b>S8774</b>	13	640	6500K	40°	120	50000	3.70	4.50	N	1.44	045923087745	10045923087742

Pack Type: Box / Inner Pack 6 / Master Pack 24

