

LED PAR38 Lamp



SATCO High Performance LED PAR38 lamps, feature a "High Power Chip" configuration specifically designed to illuminate objects, displays, showcases, etc. Delivering comparable light output to halogen "PAR38" lamps. The LED PAR38 design directly replaces existing halogen lamps and maintains the lamps proportions in the luminaire while optimizing performance.

Applications

- Display & showcase lighting
- Recessed & track lighting
- Retail merchandising



LED PAR38 Lamp

Features and Benefits

- Long life – 50,000 hours
- High efficiency – only 17 watts
- Offered in 3200K & 6500K
- Attractive design – seamless integration
- No IR or UV – protects valuable objects
- Instant on at full brightness
- Mercury free – environmentally positive
- Very low maintenance costs
- Reduces cooling costs – generates very little heat
- 3 year warranty
- C.U.L. listed



LED PAR38 – E26 Base

Specifications

Parameter	Unit	Specification			
Color Temperature	K	3200K		6500K	
Beam Angle	deg.	25°	40°	25°	40°
Power Consumption	W	17			
Operating Voltage	V	120			
Luminous Flux	lm	760	760	850	850
Life Time	Hrs.	50000			
Dimensions	inch	Ø4.76" W x 5.46" H			
Base		E26			
Color Rendering Index	Ra	83		76	
Item No.		S8751	S8753	S8752	S8754

Illumination

Throw Distance	6500K – 25°		3200K – 25°		6500K – 40°		3200K – 40°	
	Beam width	Luminance (lux)	Beam width	Luminance (lux)	Beam width	Luminance (lux)	Beam width	Luminance (lux)
3.5 Ft.	1.48 Ft.	10517	1.48 Ft.	8605	2.00 Ft.	7650	2.00 Ft.	5875
6.5 Ft.	2.46 Ft.	2726	2.46 Ft.	2151	2.79 Ft.	1920	2.79 Ft.	1500
9.8 Ft.	3.11 Ft.	1257	3.11 Ft.	966	3.83 Ft.	850	3.83 Ft.	650

Item No.	Watt	Lumens	CCT	Beam	Volt	Life/ Hrs.	M.O.D.(Inches)	M.O.L.(Inches)	ES	CUFT.	Unit UPC	Case UPC
S8751	17	760	3200K	25°	120	50000	4.76	5.46	N	2.49	045923087516	10045923087513
S8752	17	850	6500K	25°	120	50000	4.76	5.46	N	2.49	045923087523	10045923087520
S8753	17	760	3200K	40°	120	50000	4.76	5.46	N	2.49	045923087530	10045923087537
S8754	17	850	6500K	40°	120	50000	4.76	5.46	N	2.49	045923087547	10045923087544

Pack Type: Box / Inner Pack 6 / Master Pack 24

