

LED	25,000 Hours average rated life, 120 Volts
------------	--

Catalog Number	
Notes	Type

Applications:

Ideal for dimmable BR40, BR30, AND R20 flood and spot light applications.

- + Recessed Downlights
- + Track Lights
- + Display Lights
- + Outdoor Fixtures That Protect From Elements



Features and Benefits

- 65W & 85W BR30/BR40 & 50W R20 replacement.
- Exceeds all industry standards – submitted for ENERGY STAR testing .
- Smooth, uniform dimming from 100% - 0.5%.
- Highly efficient LEDs and Driver.
- Long Life: 25,000 hours.
- Consistent color within 3 MacAdam ellipse tolerance.
- UL approved for damp locations.

Specifications

Item #	Description	Wattage	Voltage	Lumens	LPW	CRI	CCT	Base	MOL	Dia.
LED11E26BR3027K	LED 11W BR30 Flood - 2700K	11	120	650	59.1	85	2700K	E26	5.4	3.8
LED14E26BR3027K	LED 14W BR30 Flood - 2700K	14	120	850	60.7	85	2700K	E26	5.4	3.8
LED11E26BR4027K	LED 11W BR40 Flood - 2700K	11	120	650	59.1	85	2700K	E26	6.6	5.0
LED14E26BR4027K	LED 14W BR40 Flood - 2700K	14	120	850	60.7	85	2700K	E26	6.6	5.0
LED9E26BR2027K	LED 9W BR20 Flood - 2700K	9	120	500	55.6	85	2700K	E26	2.5	2.5

