



Green Electrical Supply

maximize your green[®]

www.GreenElectricalSupply.com



S18451

13T8/U1-G13/LED/835/DUAL
13 watt T8 U-Bend LED; 50000 Average rated hours; Medium bi-pin base; 1800 lumens; 3500K



Features

- Direct replacements for fluorescent T8 u-bend lamps in existing fixtures with or without ballasts
- Ballast compatible and ballast bypass in one lamp
- Bypass mode works in single or double ended wiring
- 120-277V in bypass mode
- NSF Approved

View:

[Ballast Compatibility Chart](#)
[Emergency Ballast Compatibility Chart](#)

S18451

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S18451	045923184512	120-277	13	50/60Hz	31W	0.90	T8
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing
Medium Bi-Pin	G13	13T8/U1-G13/LED/835/DUAL	Non-Dimmable	White	22.59"	1.00"	1.625"
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack
1800	50000	3500	Neutral White	80	160	-20C (-4F) to a maximum of +45C (+113F)	24
Package Type	CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Box	Lawful for sale in California	PLNGZPZ9UOHF DLC Search	Plastic	Yes	Yes	cULus Listed for Type A; cULus Classified for Type B - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

